

PCA Consolidate & Seal™

CONSOLIDATE & SEAL™ is a ready to use penetrating treatment that binds and hardens porous and granular surfaces together.

CONSOLIDATE & SEAL™ has been formulated and laboratory tested for the specific application around swimming pools, building facades and coastal property surfaces to prevent salt attack and water absorption. Ideal for both internal and external use.



- SANDSTONE
- TRAVERTINE
- GRANITE

- LIMESTONE
- TERRACOTTA
- CONCRETE

- BRICKS
- WET & DRY CAST PAVERS

- Strengthens natural stone
- Allows surface to breathe
- Low molecular for optimum penetration
- Quick dry formulation
- Clear and invisible protection
- Permits vapour transmission
- Internal and external use
- User friendly and easy to apply
- Mould and mildew resistant
- Resists UV Degradation

SURFACE PREPARATION AND APPLICATION / DIRECTION FOR USE

Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence and laitance before applying CONSOLIDATE & SEAL™.

1. Ensure the surface is clean and dry.
2. Cover surfaces not intended to be treated.
3. Saturate an even first coat using a sprayer, lambswool applicator or paint brush including under the pool coping. It is recommended to use a pump sprayer on rough surfaces.
4. Allow sealer to penetrate the surface for 10 - 15 minutes.
5. The following coats should be applied evenly before the first coat is fully dry
6. After final application, thoroughly wipe all excess sealer with clean and absorbent towels.
7. A full cure is achieved in 28 days, however, can be put to service in 14 days. It is important that no water comes into contact with newly sealed surfaces for at least 2-3 days after application.
8. Clean tools used during application with solvent

Dip sealing is required and recommended for optimum protection against salt attack, mainly in direct contact with environments such as pools and coastal properties. For vertical surfaces, it is recommended to apply 4 x light coats to prevent product runoff.

COVERAGE

Application rate depends on the porosity of the surface, temperature and method of application and ranges between 0.5 - 4 sqms per litre.

Always do a test first in an inconspicuous area to ensure suitability and satisfactory results.

MAINTENANCE

Use STONE SOAP™ for daily/weekly cleaning.

Use STONE DEGREASER™ for stain spot cleaning and periodical cleans.

CLEAN UP

Thoroughly rinse application equipment with methylated/ white spirits or solvents.

DISPOSAL

CONSOLIDATE & SEAL™ must be disposed of according to local, state and federal regulations.

SAFTEY NOTES

For more specific and further information regarding the handling of this product, please refer to the Safety Data Sheet.

Premium Coatings Australia (PCA) warrants to the original consumer / purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of 52 weeks from the date of original purchase. PCA's sole liability under this warranty shall be limited to the replacement of the product. This warranty will not apply to any product which has been modified in any way or which has not been used in accordance to the manufacturer's instructions. This warranty does not cover product damaged before installation, mishandling, incorrect installation, normal wear and tear or incorrect cleaning / maintenance procedures. PCA makes no other warranties either expressed or implied. This warranty gives the purchaser specific legal rights and is not transferable.



**FORMULATED & MANUFACTURED
IN AUSTRALIA FOR
AUSTRALIAN CONDITIONS**

WWW.PREMIUMCOATINGS.COM.AU

1300 220 337 | sales@premiumcoatings.com.au | Unit 1C/62 Heathcote Road, Moorebank, NSW 2170