

PCA RockHard™

ROCKHARD™ is a commercial grade hardener / densifier providing new and old or existing concrete with a dust proof, waterproof, chemical and moisture resistant surface.

A quick dry and water-based technology ensures an ease of application internally and externally, making it also ideal for concrete polishing.



- CONCRETE WALLS
- CONCRETE FLOORS

- WAREHOUSE FLOORS
- CONCRETE DRIVEWAYS

- TERRAZZO TILES
- TERRAZZO IN SITU

- Increases life expectancy of concrete surfaces
- Internal and external use
- Water based formula
- Natural Look
- Deep penetrating for long term performance
- Ideal for concrete polishing on new and old surfaces
- Increases surface hardness with clear protection
- Mould, Mildew, Oil and water resistant
- Reduces porosity and permeability

SURFACE PREPARATION AND APPLICATION / DIRECTION FOR USE

Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence and laitance before applying ROCKHARD™.

If strong acidic or caustic cleaners are used, neutralise the surface with a diluted solution of STONE DEGREASER™, thoroughly and completely wash/rinse to remove any residues.

1. Ensure the surface is clean and dry
2. Cover surfaces not intended to be treated.
3. Apply an even first coat using a low-pressure sprayer or a lambswool applicator.
4. Allow product to penetrate the surface for 15-20 minutes and thoroughly wipe all excess with clean and absorbent towels.
5. The second coat should be applied evenly after the initial application as directed in steps 3-4.
6. After final application, thoroughly wipe all excess with clean and absorbent towels.
7. Should a product residue appear (white), agitate the surface with a white nylon scrubbing pad to loosen the residue.
8. A full cure is achieved in 24 - 72 hours. Foot traffic can resume in 8 hours, driving in 24 hours.
9. It is important that no water comes into contact with newly sealed surfaces for at least 24 hours after application.
10. If polishing is required after treatment, continue the process of grinding, honing and polishing progressively with a finer diamond pads until high gloss finish is achieved.
11. Clean tools used during application with water.



Always do a test first in an inconspicuous area to ensure suitability and satisfactory results.

COVERAGE

Application rate depends on porosity of the tile or paver, temperature and method of application and ranges between 5 - 20 SQMs per litre.
USE AS IS, DO NOT DILUTE.

MAINTENANCE

Use STONE SOAP™ for daily/weekly cleaning.

Use STONE DEGREASER™ for stain spot cleaning / machine scrubbing and periodical cleans.

CLEAN UP

Thoroughly rinse application equipment with water. Uncured material may be removed with warm water and detergent.

DISPOSAL

ROCK HARD™ must be disposed of according to local, state and federal regulations.

SAFTEY NOTES

For more specific and further information regarding the handling of this product, please refer to the Safety Data Sheet.

Premium Coatings Australia (PCA) warrants to the original consumer / purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of 52 weeks from the date of original purchase. PCA's sole liability under this warranty shall be limited to the replacement of the product. This warranty will not apply to any product which has been modified in any way or which has not been used in accordance to the manufacturer's instructions. This warranty does not cover product damaged before installation, mishandling, incorrect installation, normal wear and tear or incorrect cleaning / maintenance procedures. PCA makes no other warranties either expressed or implied. This warranty gives the purchaser specific legal rights and is not transferable.



**FORMULATED & MANUFACTURED
IN AUSTRALIA FOR
AUSTRALIAN CONDITIONS**

WWW.PREMIUMCOATINGS.COM.AU

1300 220 337 | sales@premiumcoatings.com.au | Unit 1C/62 Heathcote Road, Moorebank, NSW 2170